

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
27 March 2003 (27.03.2003)

PCT

(10) International Publication Number  
**WO 03/025574 A1**

(51) International Patent Classification<sup>7</sup>: **G01N 33/543**,  
33/52

(21) International Application Number: PCT/US02/29327

(22) International Filing Date:  
17 September 2002 (17.09.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/323,426 17 September 2001 (17.09.2001) US  
10/217,337 12 August 2002 (12.08.2002) US

(71) Applicant (for all designated States except US): **AMIRA MEDICAL** [US/US]; 9115 Hague Road, Indianapolis, IN 46256 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **DOUGLAS, Joel**, S. [US/US]; 25285 La Loma Drive, Los Altos Hills, CA 94022 (US). **PEREZ, Edward, P.** [US/US]; Apt. H, 799 Berkeley Street, Menlo Park, CA 94025 (US).

(74) Agents: **SCHMAL, Charles, P.**; Woodward, Emhardt, Naughton, Moriarty & McNett, Bank One Center/Tower, Suite 3700, 111 Monument Circle, Indianapolis, IN 46204 et al. (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: **EMBOSSED TEST STRIP SYSTEM**



(57) Abstract: A bodily fluid sampling device includes a support member (216) that defines an aperture (218) to receive a bodily fluid sample and a cover member (15). A test strip (200) is compressed between the support member (216) and the cover member (15) to form an embossed pillow (221) within the aperture (218). The embossed pillow (221) is adapted to absorb the bodily fluid sample. The test strip (200) has an incision surrounding the embossed pillow (221) to minimize leakage of the bodily fluid sample from the embossed pillow (221). The support member (216) can further include a blade (220) that surrounds the aperture (218) to form the incision around the embossed pillow (221).



WO 03/025574 A1

WO 03/025574 A1



---

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## **EMBOSSSED TEST STRIP SYSTEM**

### **REFERENCE TO RELATED APPLICATIONS**

5

The present application claims the benefit of U.S. Provisional Patent Application No. 60/323,426 filed September 17, 2001, and the present application is a continuation-in-part of U.S. Patent Application Serial No. 09/658,000 filed September 8, 2000, which is a continuation U.S. Patent Application Serial No. 10 09/215,686 filed December 18, 1998, now U.S. Patent No. 6,162,639, which claims the benefit of U.S. Provisional Patent Application Serial No. 60/068,307 filed December 19, 1997, all of which are incorporated by reference in their entirety.

15

### **FIELD OF THE INVENTION**

The present invention relates to a system and method for determining the presence or concentration of analytes or biological agents in a sample of bodily fluid using a specific amount of membrane imbided with dry reagent. In the most preferred embodiment the meter and a single use, reagent bearing test strip is used 20 to measure the concentration of glucose in a bodily fluid such as whole blood or interstitial fluid (ISF).

### **BACKGROUND OF THE INVENTION**

25

The need for simple methods to determine the chemical and biological constituents in bodily fluids has increased as point of care testing has gained in popularity. The most common application is the self monitoring of blood glucose concentrations by patients with diabetes. Diabetic patients frequently administer 30 insulin or take other therapeutic actions based on the test results. As testing is

generally recommended multiple times daily and may occur in any setting, an easy to use, low sample volume test is required. The issues associated with sample volume are significant to many diabetic patients, especially elderly patients with compromised circulatory systems.

5

In addition to chronic disease monitoring, there are other applications where simple, low sample size testing at the point of care may be desired. For example, many practitioners believe that certain medications could be administered much more effectively, both from a medical outcome and from a cost perspective, if the circulating level of such medications could be monitored during the course of treatment. Generally, if the level of an analyte or biological agent is important enough, the patient needs to go to a clinic or laboratory and submit to a venipuncture so a test may be run on an expensive clinical instrument. The ability to monitor the patient either in the doctor's office or at home could lead to improved outcomes. By providing a simple low sample volume test, the practitioner is given a means of performing a test utilizing a small sample which in most cases is easier to obtain from the patient by using a simple finger stick.

The National Institute of Health conducted a large scale study to evaluate the benefit of long term tight control of the blood glucose for the diabetic patient. The study, known as the DCCT, proved that long term tight control of the blood glucose levels in patients had a direct relationship to the health of the patient. One way for the medical profession to monitor the control of a patient is for the patient to use a blood glucose monitoring system. One of the main obstacles to testing is the sample size needed to perform the test. As patients age and their circulation decreases, the ability to extract an adequate sample of body fluid is affected. A test which more efficiently utilizes the bodily fluid would aid in reducing the problems associated with larger sample size tests. Current blood glucose monitoring devices such as the One Touch systems manufactured by LifeScan, Inc. of Milpitas, Calif. require the patient to place between 8 and 12 microliters of blood on the test strip.

30

Many patients apply substantially more blood to the test to minimize the failure of the test due to not having enough sample applied to the strip. This unmeasured sample leads to accuracy problems due to more sample than dried chemistry present on the test strip. A system which self meters the amount of sample to a  
5 specific amount of carrier consisting of a matrix which holds a relatively constant amount of chemistry and provides a consistent volume for absorbing the sample to promote the test reaction would be a significant advancement to the patient community.

10 Many diabetics currently use a test method described in U.S. Pat. No. 5,304,468 Phillips et al. This system is comprised of an electronic meter and a disposable reagent strip. The meter reads the color change of the strip which correlates to the concentration of the analyte in the sample applied to the strip. The meter is an expensive and complex instrument which uses multiple light sources or  
15 detectors to isolate the reagent color change from the sample color. The user must select the calibration code for the meter to match the calibration code of the test strips. In this way, the meter accommodates a wide range of test strip performance values.

20 U.S. Pat. No. 4,637,403, to Garcia et al., describes an integrated system which provides a method by which the patient lances the finger to get a sample of blood which is then used by the device to read the quantity of analyte in the sample. This system uses a complex reflectance system to read the analyte level in the sample.

25 U.S. Pat. No. 5,279,294, to Anderson et al., describes a hand held, shirt pocket device for quantitative measurement of glucose or analytes in biological fluids. The device has a sophisticated electronics system and a sampling system integrated into one device to determine the quantity of analyte in a bodily fluid  
30 sample

U.S. Pat. No. 5,515,170, to Matzinger et al., describes the difficulties of keeping a strip holder and optics system clean and the need to present the test strip in the proper perspective to the optics.

5

European Patent Specification 0 351 891 B1, to Hill et al., describes an electrochemical system and electrodes which are suitable for the in vitro determination of blood glucose levels. The system requires the use of expensive electrodes and a sophisticated reader to determine blood glucose levels.

10

U.S. Pat. No. 4,994,167, to Shults et al., describes a measuring device for determining the presence and amount of a substance in a biological fluid using electrochemical methods. This system requires a complex instrument and method for the patient to determine the quantitative result.

15

U.S. Pat. No. 5,580,794, to Allen et al., describes a single use disposable measuring device for determining the presence and amount of a substance in a biological fluid using reflectance methods. This system utilizes optics and electronics packages which are mated in a single plane.

20

Single use disposable devices have been designed for the analysis of analytes in bodily fluids. U.S. Pat. No 3,298,789, to Mast, describes a system in which whole blood is applied to a reagent strip. After a precise, user-timed interval, the blood must be wiped off by the user. An enzyme system reacts with the glucose present in the sample to create a color change which is proportional to the amount of glucose in the sample. The strip may be read visually by comparing to a printed color intensity scale, or in an electronic instrument.

25

U.S. Pat. No. 5,418,142, to Kiser et al., describes a single use device which does not require blood removal or color matching. The amount of analyte present in the sample is read in a semiquantitative fashion.

5 U.S. Pat. No. 5,962,215, to Douglas et al., describes a series of semiquantitative, single use devices which are used to determine the level of an analyte in a biological sample. These devices do not require blood removal or color matching.

10 U.S. Pat. No. 5,451,350, to Macho et al., describes a single use system for the determination of an analyte in a biological sample.

European Patent Application No. EP 0 759 555 A2, to Douglas et al., describes a multilayer reagent test strip which measures the concentration of  
15 analyte in a liquid sample that is applied to it.

U.S. Pat. No. 4,994,238, to Daffern et al., describes a multilayer test device which uses a defined area of absorbent, reagent bearing matrix.

20 Although many improvements have been made, the cost and complexity of measuring analyte levels in biological samples remains a significant issue for patients and for the health care system. The need to deliver a sizable sample of bodily fluid to the strips or electrodes in use leads to errors in performance and presents problems for the patient. The availability of a low sample volume which  
25 meters the sample to the test matrix reduces the issues with short sampling or over sampling of the test. This is a great advantage to the patient to insure an accurate test. A simplified quantitative test system of this invention for the periodic monitoring of constituents of biological fluids, such as glucose in blood, would make testing more accessible to patients and would improve their well-being.

A system which requires a smaller fluid sample is attractive to many patients. There has been a trend toward smaller sample sizes, but most devices still require about 10  $\mu\text{L}$  of blood. Many patients have difficulty routinely applying an adequate sample to the strips or electrodes. Inadequate sampling can cause erroneous results or may require that the user discard an expensive test strip and repeat the sample application procedure. A system which would require about 3  $\mu\text{L}$  or less, which is a fraction of the volume required for most blood glucose tests and could be more readily obtained by patients, would be advantageous.

10        An object of the present invention is to provide a method for measuring the amount of analyte in a sample of biological fluid using a simple, low sample volume, reagent test strip with a built in metering system.

15        Another object of this invention is to provide reagent test strips that can meter the sample into the reaction matrix.



## SUMMARY OF THE INVENTION

The method of this invention involves the use of single use test strips  
5 capable of reading small sample sizes and determining the amount of an analyte in  
the small sample. The low sample size feature of the strip permits the patient to  
use less invasive systems to acquire a sample than the 21 gauge lancing devices in  
current use. The device is structured with a capillary to meter a specific quantity of  
10 sample to the test matrix, thereby eliminating a significant source of error  
associated with short sampling. The capillary is designed so that, when placed in  
contact with a sample of bodily fluid, it transfers the sample to the test matrix. If  
the sample is insufficient to travel the full length of the capillary, then the sample  
does not reach the test matrix and will not wick into the test matrix, which prevents  
15 the patient from short sampling the test strip. The user can add additional sample  
to the capillary to complete the test. Once the sample contacts the test matrix, the  
sample will wick into the test matrix until the test matrix is filled, then stop.  
Excess sample remains in the capillary and serves as a signal to the patient that the  
test matrix has the correct amount of sample for the test. This provides many  
advantages to the patient including the elimination of wasted strips due to short  
20 sampling which results in a substantial cost savings for the patient and reduces the  
number of inaccurate tests from marginal samples.

The capillary design also provides another interesting benefit. As blood  
travels down through the capillary to the test area, the blood warms the peg, thus  
25 regulating the temperature of the strip and the test. This is beneficial in two ways;  
the first is that each test is performed under somewhat controlled conditions,  
regardless of whether or not the surrounding temperature is warm or cold. Second,  
this effect alleviates the problem of fogging over the test area. This is a problem  
with many blood glucose monitors when testing in cooler ambient conditions.

The formation of a captivated microtitration zone is described in U.S. Pat. No. 5,872,713 Douglas et al. When constructed according to this invention, the microtitration zone can be achieved with a specific volume by following a simple series of steps: (a) applying a specific amount of reagent such that it does not saturate the matrix and is developed to indicate a specific analyte, (b) drying the reagent so that the active ingredients adhere to the substrate of the matrix, (c) embossing or compressing the matrix to collapse the matrix surrounding the reaction zone so that the void volume of the resulting test matrix microtitration volume is approximately equal to the sample size desired, (d) installing it into a performed pocket which completely surrounds all the circumference of the pillow where the capillary is in communication with the top side/sample side of the pillow, and (e) sealing the system together. The embossed/collapsed areas have had their void volume reduced to approximately zero and the test matrix reaction zone forms a small bibulous pillow which retains its void volume and has the desired total volume. This limits the ability of the reagents imbibed into the embossed matrix to participate in the reaction of the result zone. The test pad can be made from various matrix materials which will hold the test reagent in a dried form including polyethersulphone (Gelman sciences Supor 200D), polysulphone (Memtec filtration asymmetric membrane) and nylon (Pall biodyne). The wicking material which can be selected from various materials, including Pall Accuwick and Whatman 41, which provide a high enough capillary action to wick and absorb the sample from the capillary peg and spread it into and fill the reaction matrix microtitration volume.

The applied bodily fluid reacts with the reagents impregnated in the test pad within the test strip and the resulting color change is read by the optics system of the meter adapted to read the strip.

The patient uses the test strip by removing it from the packaging and placing it into a meter designed to utilize the test strip. The patient turns the meter

on or it can be automatically started from the test strip insertion. The patient uses either a sampler from the kit or one procured separately to draw a sample of capillary blood. This sample is applied to the test strip, the meter reads the sample, and the meter displays the result after an appropriate time.

5

One aspect of the present invention concerns a bodily fluid sampling assembly. The assembly includes a support member that defines an aperture adapted to receive a bodily fluid sample and a cover member. A test strip is compressed between the support member and the cover member to form an embossed pillow within the aperture. The embossed pillow is adapted to absorb the bodily fluid sample. The test strip has an incision surrounding the embossed pillow to minimize leakage of the bodily fluid sample from the embossed pillow.

Another aspect of the present invention concerns a test strip assembly that includes a wicking layer for collecting a bodily fluid sample and a support member. The support member defines an opening and has a blade extending around the opening. The blade contacts the wicking layer to minimize flow of the fluid sample in the wicking layer from the opening.

A further aspect of the present invention concerns a test strip. The test strip includes a test matrix to test a bodily fluid sample. A wicking layer is provided over the test matrix. The wicking layer has an embossed pillow for absorbing the bodily fluid sample. The wicking layer has an incision surrounding the embossed pillow to minimize leakage of the bodily fluid sample from the embossed pillow.

25

Other forms, embodiments, objects, features, advantages, benefits and aspects of the present invention shall become apparent from the detailed drawings and description contained herein.

### BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is an exploded, side elevation view of one embodiment of a test pad  
5 matrix and wicking layer prior to being embossed in a die formed by plates.

FIG. 2 is a cross-sectional view of one embodiment of a test pad matrix and wicking layer during embossing in a die formed by plates.

FIG. 3 is an exploded perspective, cut away view of the test pad matrix, wicking layer and upper and lower plates of the embossing die.

10 FIG. 4A is an assembled view and 4B is an exploded perspective view of one embodiment of the strip showing assembly of the handle, test pad, wicking layer, and capillary.

FIG. 5 is an enlarged, cross-sectional view of a test strip constructed according to the present invention.

15 FIG. 6 is an exploded, cross-sectional view of an alternative embodiment of the test strip in accordance with the present invention.

FIG. 7 is a cross-sectional side view of the alternative embodiment of the test strip as assembled.

20 FIG. 8 is an exploded, cross-sectional side view of another alternative embodiment of a test strip in accordance with the present invention.

FIG. 9 is a cross-sectional side view of the test strip of Figure 8 as assembled for use.

FIG. 10 is an enlarged, cross-sectional view of a test strip constructed according to another embodiment of the present invention.

## DESCRIPTION OF SELECTED EMBODIMENTS

For the purposes of promoting an understanding of the principles of the invention, reference will now be made to the embodiments illustrated in the drawings and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the invention is thereby intended, such alterations and further modifications in the illustrated device, and such further applications of the principles of the invention as illustrated therein being contemplated as would normally occur to one skilled in the art to which the invention relates. One embodiment of the invention is shown in great detail, although it will be apparent to those skilled in the art that some of the features which are not relevant to the invention may not be shown for the sake of clarity.

15

The present invention provides improvements over existing technology in use today in several ways. A preferred embodiment of the invention creates a microtitration zone which permits the accurate testing of a small fluid sample and prevents oversampling, while the integrated capillary provides a means to eliminate the problems associated with short sampling which frequently occurs in the current commercial products. The capillary also provides a means of absorbing the fluid sample from a non-fingerstick location. This permits the use of non-traditional lancing systems. The small test pad used in this invention reduces the cost of the matrix employed and the quantity of expensive reagents needed to conduct an accurate assay using an oxidase and peroxidase chemistry. With a smaller test pad, a smaller sample volume is adequate. It should be noted also that an electrode based test system could be used with the basic structure and elements of this invention. A further feature of the capillary is that the capillary acts as a retaining chamber where a sample of appropriate volume is initially collected and then delivered to the test pad. The sample is only delivered to the test pad when a

30

sufficient amount of sample has been collected within the capillary. Furthermore, the capillary may be constructed to further include a fluid chamber. The fluid chamber may be disposed adjacent the test media, such that in use, the distal end of the capillary is placed in contact with a bodily fluid to be sampled. The bodily fluid is received within the capillary through capillary action or other means such as a wicking material. As bodily fluid is drawn into the capillary the bodily fluid fills the fluid chamber. After the fluid chamber is filled, the sample of bodily fluid collected in the fluid chamber may then be deposited upon the test media. A benefit of using a fluid chamber is that a smaller sized sample may be utilized to perform a desired test because the entire amount of bodily fluid needed for the test can be accurately delivered to a test site, thereby reducing the overall amount of sample needed to perform the test. Furthermore, the use of a fluid chamber to collect the sample may also lead to fewer failed tests due to inadequate sample volume, because the sample will not be delivered to the test media until a sufficiently sized sample is collected.

Although the fluid chamber has been described in use with a capillary, it is contemplated that other collection devices may be utilized with the fluid chamber of the present invention. For example, the fluid chamber may be included within a test strip wherein the sample is placed on a portion of the test strip and transported to the fluid chamber. The descriptions above should not be considered limiting and are intended to be exemplary.

The test strip is comprised of a test pad situated in a test pad holder. This holder provides a means for accurately positioning the test pad with respect to the optics system in the meter and for providing a means for blocking ambient light from affecting the analysis. The test pad is impregnated with the appropriate chemistry to permit a colorimetric analysis of the analyte being tested, and must therefore provide a stable absorbent substrate. If the system is developed with an electrode based system, the function of the test pad holder is to position the

electrode contacts on the strip with those corresponding to the meter. The test pad can be made from various materials which will hold the test reagent in a dried form, including polyethersulphone (Gelman Sciences Supor 200D), polysulphone (Memtec filtration asymmetric membrane) and nylon (Pall Biotec). The wicking  
5 layer can likewise be selected from various materials, including Pall Accuwick and Whatman 41, which provide a high enough capillary action to absorb the sample and spread it to the reaction matrix.

The test strip of this invention provides a support for the test pad and the  
10 capillary peg contacting the test pad. The peg positively seats in the meter in a detent and is locked from rotation by a corresponding key in the test strip which fits into a slot in the meter test strip holder. The test strip holder is positioned to the optics block using pins on the optics block assuring proper alignment of the test strip. It also seals the optics area from ambient light and any excess blood  
15 contamination. These features are more fully disclosed in U.S. Pat. No. 5,872,713, which is incorporated herein by reference.

The signal producing system impregnated in the test pad matrix can be formed from different indicator systems, such as 3-methyl-2-benzothiazolinone  
20 hydrazone (MBTH) and 8-anilino-1-naphthalenesulfonate(ANS) [U.S. Pat. No. 5,453,360 to Yu], MBTH and 3-dimethylaminobenzoic acid (DMAB) [U.S. Pat. No. 5,049,487 to Phillips et al.],  
3-methyl-2-benzothiazolinone-hydrazone-sulfonate sodium salt (MBTHS) and  
-Ethyl-N-(3-sulfopropyl)aniline (ALPS) [U.S. Pat. No. 4,396,714 to Maeda et al.].  
25 One skilled in the art could devise an alternate indicator system. The oxidase enzyme system contained in the reagent pad produces hydrogen peroxide which is used to convert the indicator with the assistance of peroxidase which acts as the catalyst.

In the most preferred embodiment the reagents are impregnated into a porous membrane by submerging the dry membrane into a reagent dip. Excess fluid is wiped from the membrane surface and the membrane is gently dried in an oven. At this point, subsequent dipping and drying can be conducted. A preferred  
5 embodiment for a two dip process is:



**MBTHS & ALPS Formulation**

Final  
Concentrations

5

**A Dip**

	In Citrate buffer, pH 7	0.1 M
	stock A Dip	
10	EDTA	0.08%
	mannitol	0.19
	Gantrez-S95	0.53%
	Klucel 99-EF	20 uM
	Crotein-SPA	7.45%

15

**enzyme reagents**

	Glucose Oxidase	0.92%
	Peroxidase	0.54%

20

**B Dip**

	In 70% Ethanol	
25	MBTHS	0.66%
	ALPS	2.00%
	SOS	0.20%

30 The color formed after applying the bodily fluid to the reagent test pad is  
proportional to the amount of analyte in the applied sample. The meter measures

the change in reflectance due to the development of the specific color generated by the indicator. This is either used as the input to a function which relates reflectance to analyte level or to a table which correlates reflectance value to analyte level.

The function or the table is stored within the meter system for it to produce and display a reading of the analyte level. While most meters in use today employ functions to convert reflectance readings to analyte concentration, this approach requires that the function be stable and well understood. The use of a look up table permits the storage of specific values for reflectance and their corresponding analyte levels. The meter uses this table and interpolates between the table values to give relatively accurate readings. This is achievable in a system such as that described by this invention as the table can quickly be generated for each reagent lot produced. The devices of this invention using a read-once calibration chip, or being fully disposable, can use a lot- specific look up table to convert reflectance reading to analyte levels.

FIG. 1 shows an elevation view of the un-embossed layers, wicking layer 5, test matrix layer 4, and top layer 1 between the die 17 formed from top plate 16 containing hole 18 and bottom plate 15 containing hole 18A.

FIG. 2 shows an elevation view of the embossed or compressed layers, wicking layer 5, test matrix layer 4, and top layer 1 between the die 17 formed from top plate 16 containing hole 18 and bottom plate 15 containing hole 18A. Hole 18 in die plate 16 forms the microtitration pillow 21 in the wicking layer 5 and in test matrix layer 4. The areas of the layers surrounding pillow 21 are compressed to make them essentially impervious to sample liquid flow, thus forming the microtitration volumetric area around pillow 21. Hole 18A allows for the test strip to be placed in an optical meter whereby a color change of the top layer and/or matrix layer can be measured.

FIG. 3 shows an exploded perspective view of the embossed or compressed layers, wicking 5, test matrix 4, and top layer 1 as formed between the die 17 formed from top plate 16 and bottom plate 15 containing hole 18A.

5           The assembly of a test strip 20 shown in FIG. 4A is accomplished as shown in FIG. 4B. In a preferred embodiment bottom or support member 6 which has the capillary peg 7 and capillary 10 integrally molded therein (e.g., by injection molding) and constructed so that microtitration pocket 8 has breather holes 9 located within the microtitration pocket 8. Or capillary peg 7 can be formed as a  
10       separate element and assembled into support member 6 if desired. FIG. 2 shows the formation of the microtitration pillow 21 in matrix 4 and wicking layer 5. The microtitration pillow 21 is formed using die 17 formed from top plate 16 and bottom plate 15. By using a die to form the pillows the spacing of the pillows 21 can be formed in the matrix 4 and wicking 5 so that they align with the  
15       microtitration pocket 8. When the top layer 1 is assembled on bottom member 6 with test matrix layer 4 and wicking layer 5 properly positioned as shown between layers 1 and 6. Test matrix pad 4 is formed from a bibulous matrix which has been impregnated with a reagent system comprised of enzymes, indicators and blood separation agents and the wicking matrix pad 5 provides a means of spreading the  
20       sample over the test pad 4. Layers or pads 4 and 5 are preferably embossed or compressed prior to assembly with layers 1 and 6. The holes 22 and 23 formed in the top layer 1 and alignment keys 11 and 12 formed in holder 6 provide a means of aligning the test strip assembly including pillow 21 and hole 18A to the microtitration pocket 8. The breather holes 9 provide an escape path for trapped  
25       air in the assembly pillow 21 when wicking the sample up the capillary 10 and into pillow 21. Figure 5 shows an additional preferred feature of the present invention where capillary peg 7 and capillary tube 10 are formed with a protruding collar 25 extending from capillary tube 10 to engage and further compress pillow 21. This feature provides a seal between capillary tube 10 and the surface of wicking layer  
30       5, which better forces the sample flow from capillary tube 10 into the interior of

wicking layer 5 to better distribute the sample throughout test matrix layer 4 and completely fill microtitration volume 8 and to better prevent sample from flowing between the surface of wicking layer 5 and the surface of the end of capillary peg 7.

5

Figures 6 and 7 illustrate a test strip 200 according to another embodiment of the present invention. The test strip 200 includes a top layer 1, a test matrix 204 and a wicking layer 205 of the type as described above. As shown, the test matrix 204 is sandwiched between the top layer 201 and the wicking layer 205. Layers 10 204 and 205 as well as the test matrix 204 are pressed between a bottom plate (cover member) 15, and a top plate (support member) 216. When pressed together, plates 15 and 216 form a die 217 with plates 15 and 216 each defining openings 18A and 218, respectively. In one embodiment, openings 18A and 218 have a generally cylindrical shape. However, as should be appreciated, openings 18A and 15 218 can be shaped differently. Bodily fluid samples are collected through the opening 218 in the top plate 216, and the opening 18A in the bottom plate 15 allows the sample collected on the test matrix 204 to be analyzed.

As shown in Figure 7, plate 216 has an interior surface 219 with a blade 20 220 projecting therefrom towards plate 15. In one embodiment, the blade 220 is integrally formed with the top plate 216, and in another embodiment, the blade 220 is a separate component attached to plate 216. During assembly, the top plate 216 and the bottom plate 115 are compressed to make the portion of the wicking layer 205 and the test matrix 204 adjacent the aperture 218 virtually 25 impervious to a bodily fluid sample. Within the opening 218 in plate 216, the wicking layer 205 and the test matrix 204 are embossed to form a microtitration area or pillow 221, which is able to absorb the fluid sample. Moreover, the blade 220 in one embodiment presses into the wicking material 205 and is sufficiently sharp to form an incision or cut 222 at least through part of the wicking layer 205 30 in order to minimize the amount of fluid leakage from the microtitration pillow

221. In another embodiment, the blade 220 only compresses the test strip 200 around the microtitration pillow 221 making the periphery of the microtitration pillow 221 impervious to fluid so as to minimize fluid leakage from the microtitration pillow 221. The blade 220 in the illustrated embodiment has a generally cylindrical shape. However, it should be appreciated that the blade 220 can be shaped differently.

In one embodiment, the blade 220 has a length L that is sized to only cut the incision 222 through part of the wicking layer 205 so that the microtitration pillow 221 of the wicking layer 205 remains attached to the remainder of the test strip 200. In another embodiment, the blade 220 is sized to cut the incision 222 completely through the wicking layer 205. The microtitration pillow 221 of the wicking layer 205 in one form of this embodiment bonded to the test matrix 204, and in another form, the microtitration pillow 221 of the wicking layer 205 is retained in opening 18 through frictional engagement. In the illustrated embodiment, the blade 220 has a closed, continuous shape so that the incision 222 encircles the microtitration pillow 221. Although the incision 222 in the illustrated embodiment is continuous to minimize fluid leakage from the microtitration pillow 221, it should be understood that the incision 222 can be formed in a discontinuous manner such that fluid leakage prevention is not severely compromised. For example, the blade 220 in another embodiment can include cut out sections that form retaining webs in the wicking layer 205 such that the formed incision 222 is discontinuous.

In the illustrated embodiment, the blade 220 has a generally cylindrical shape to coincide with the shape of opening 218. As depicted in Figure 6, inner surface 224 of opening 218 is flush with inner surface 226 of the blade. With the blade 220 being flush with the opening 218, the incision 222 is formed at the periphery of the microtitration pillow 221 in order to effectively destroy the wicking function of the material adjacent the incision 222. This in turn minimizes

leakage of the fluid sample from the microtitration pillow 221. Minimizing leakage from the microtitration pillow 221 reduces the amount of fluid required for the fluid sample. Therefore, as a sample of bodily fluid is placed upon the microtitration pillow 221, the wicking layer 205 distributes the sample across the area of the opening 218, and the blade 220 acts to prevent any sample from flowing beyond it. Since the blade 220 prevents fluid from passing outside the area of the aperture 218, less fluid needs to be collected.

Referring to Figures 8 and 9, a test strip 300 according to another embodiment of the present invention includes top layer 1, test matrix layer 4 and a wicking layer 305, which is sandwiched between bottom plate 15 and top plate 16. The top plate 16, as illustrated, defines aperture or opening 18, and the bottom plate 15 defines aperture or opening 18A. In the illustrated embodiment, a fluid sample is collected on the test strip 300 through opening 18. Opening 18A enables a test device to perform a measurement upon the sample collected the test strip 300, such as a colormetric measurement in which the reflectance of the collected sample is measured in order to determine the amount of glucose in the sample.

In one embodiment, the wicking layer 305 and test matrix layer 4 are pre-embossed so as to form a microtitration pillow 321. In another embodiment, the microtitration pillow 321 is formed in the test strip 300 in opening 18 when the test strip 300 is pressed between the top plate 16 and the bottom plate 15 (Figure 9). In the illustrated embodiment, the wicking layer 305 has an incision 322 formed therein before assembly with the other layers of the test strip 300. As shown, the incision 322 only partially cuts through the wicking layer 305. It should be appreciated that in other embodiments the incision 322 can be formed completely through the wicking layer 305 and/or the test matrix 4. In one form, the incision 322 is pre-cut with a blade before assembly. However, as should be understood, the incision 322 can be fabricated in other manners. As depicted in Figure 9, the incision 322 is formed to align with and generally correspond with the shape of the

opening 18 in the top plate 16 so that the incision 322 surrounds the microtitration pillow 321 formed in the test strip 300.

5       The incision 322 formed in the wicking layer 305 interrupts fluid flow in the wicking layer 305 to the area surrounding the microtitration pillow 321. In use, a sample of bodily fluid is placed upon the wicking layer 305 whereby the sample spreads across the microtitration pillow 321. The incision 322 prevents the bodily fluid from flowing past the microtitration pillow 321 defined by the aperture 18. By not allowing the fluid sample to flow beyond the aperture 18, less fluid is  
10       wasted so that a smaller fluid sample is needed.

Figure 10 illustrates an enlarged view of a bodily fluid sampling assembly 400 incorporating test strip 200, according to another embodiment of the present invention. As illustrated, assembly 400 includes a support member 406 that has  
15       capillary peg 7, cover member 15, and test strip 200 sandwiched between the support member 406 and the cover member 15. The support member 406 defines a microtitration pocket 8 that fluidly communicates with a capillary tube 10 integrally formed within the capillary peg 7. The capillary tube 10 is used to draw a bodily fluid sample into the microtitration pocket 8. In the illustrated  
20       embodiment, the capillary peg 7 is integrally formed with the support member 406. Nonetheless, it should be understood that the capillary peg 7 can be formed as a separate component and attached to the support member 406. In Figure 10, the support member 406 has a protruding collar 25 that extends from the capillary tube 10 in the microtitration pocket 8 in order to compress the test strip 200. The  
25       support member 406 further includes a blade member 220 that surrounds and is aligned with the periphery of the microtitration pocket 8. The cover member 15 defines a sensor aperture 18A that is aligned with the microtitration pocket 8.

As described above, the test strip 200 includes top layer 1, test matrix 204  
30       and wicking layer 205. When the test strip 200 is pressed between the support

member 406 and the cover member 15, a microtitration pillow 221 in the test strip 200 is formed within the microtitration pocket 8. The protruding collar 25 engages and compresses the microtitration pillow 221 to improve the seal between the capillary tube 10 and the wicking layer 205. This configuration improves  
5 distribution of the bodily fluid sample within the test matrix 204. Further, in the illustrated embodiment, the blade 220 forms an incision 222 in the test strip 200 around the microtitration pillow 221. As discussed above, this incision 222 reduces the amount of bodily fluid required for a sample because less of the fluid is wasted by leaking from the microtitration pillow 221. In another embodiment, the  
10 blade 220 does not form the incision 222 in the test strip 200. Instead, the blade 220 compresses the periphery of the microtitration pillow 221 in order to make the periphery of the pillow 221 substantially impervious to fluid so as to minimize the amount of fluid required for a sample.

15 While the invention has been illustrated and described in detail in the drawings and foregoing description, the same is to be considered as illustrative and not restrictive in character, it being understood that only the preferred embodiment has been shown and described and that all changes and modifications that come within the spirit of the invention are desired to be protected.



What is claimed is:

1. A test strip assembly, comprising:  
a support member defining an aperture to receive a bodily fluid sample;  
5 a cover member;  
a test strip compressed between said support member and said cover member to form an embossed pillow within said aperture, said embossed pillow being adapted to absorb the bodily fluid sample; and  
wherein said test strip has an incision surrounding said embossed pillow to  
10 minimize leakage of the bodily fluid sample from said embossed pillow.
2. The test strip assembly of claim 1, wherein said support member has a blade member surrounding said aperture to form said incision in said test strip.
- 15 3. The test strip assembly of claim 1, wherein:  
said support member includes a capillary tube to collect the bodily fluid sample; and  
said aperture includes a microtitration pocket defined in said support member.  
20
4. The test strip assembly of claim 1, wherein said test strip includes:  
a wicking layer adapted to absorb the bodily fluid sample;  
a test matrix for reacting with the bodily fluid sample; and  
wherein said incision is formed in said wicking layer.
- 25 5. The test strip assembly of claim 4, wherein said incision is further formed through said wicking layer and said test matrix.
6. The test strip assembly of claim 4, wherein said test strip includes a  
30 top layer positioned between said top member and said test matrix.

7. A test strip assembly, comprising:  
a wicking layer to collect a bodily fluid sample; and  
a support member defining an opening, said support member having a blade member extending around said opening and contacting said wicking layer to  
5 minimize flow of the fluid sample in said wicking layer from said opening.
8. The test strip assembly of claim 7, wherein:  
said wicking layer defines an incision that coincides with said opening to  
minimize flow of the fluid sample in said wicking layer from said opening; and  
10 said blade member is adapted to cut said incision in said wicking layer.
9. The test strip assembly of claim 7, wherein said blade member  
compresses said wicking layer to minimize flow of the fluid sample in said  
wicking layer from said opening.  
15
10. The test strip assembly of claim 7, further comprising a capillary  
tube provided over said wicking layer to deliver the bodily fluid sample to said  
wicking layer.
- 20 11. The test strip assembly of claim 7, further comprising:  
a top layer; and  
a test matrix positioned between said top layer and said wicking layer for  
analyzing the bodily fluid sample.
- 25 12. The test strip assembly of claim 7, wherein said wicking layer has a  
microtitration pillow surrounded by said blade member.
13. A test strip, comprising:  
a test matrix to test a bodily fluid sample; and

a wicking layer provided over said test matrix, said wicking layer having an embossed pillow for absorbing the bodily fluid sample, said wicking layer having an incision surrounding said embossed pillow to minimize leakage of the bodily fluid sample from said embossed pillow.

5



14. The test strip of claim 13, further comprising a top layer covering said test matrix.

15. The test strip of claim 13, wherein said incision has a circular shape.


10



16. The test strip of claim 13, wherein said incision is continuous.


1/7

**Fig. 1****Fig. 2**



2/7

**Fig. 3**



**Fig. 4A****Fig. 4B**




**Fig. 5**

**Fig. 6****Fig. 7**



**Fig. 8****Fig. 9**

**Fig. 10**

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 02/29327

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 G01N33/543 G01N33/52

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 335 244 A (ABBOTT LABORATORIES) 4 October 1989 (1989-10-04) page 7, line 34 -page 8, line 19; claims 1-8	1-16
Y	US 4 994 238 A (DAFFERN ET AL) 19 February 1991 (1991-02-19) column 2, line 57 -column 3, line 53; claims 1-5; figure 3	1-16
Y	US 5 451 350 A (MACHO ET AL) 19 September 1995 (1995-09-19) column 10, line 32 -column 11, line 6; claims 1-8; figures 1-3	1-16
A	EP 0 759 555 A (LIFESCAN) 26 February 1997 (1997-02-26) claims 1-9; figure 4	1-16
-/-		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the International filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the International filing date but later than the priority date claimed

- \*T\* later document published after the International filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*Z\* document member of the same patent family

Date of the actual completion of the International search

24 February 2003

Date of mailing of the International search report

05/03/2003

Name and mailing address of the ISA  
European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Moreno de Vega, C

# INTERNATIONAL SEARCH REPORT

Internat. Application No.  
PCT/US 02/29327

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 99 32883 A (MERCURY DIAGNOSTICS) 1 July 1999 (1999-07-01) the whole document ---	1-16
X	US 6 162 639 A (AMIRA MEDICAL) 19 December 2000 (2000-12-19) cited in the application the whole document -----	1-16

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Internal application No

PCT/US 02/29327

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0335244	A	04-10-1989	US 4916056 A	10-04-1990
			AT 116443 T	15-01-1995
			AU 3156489 A	28-09-1989
			CA 1332807 A1	01-11-1994
			DE 68920176 D1	09-02-1995
			DE 68920176 T2	11-05-1995
			EP 0335244 A2	04-10-1989
			ES 2068844 T3	01-05-1995
			JP 1299464 A	04-12-1989
			JP 2818191 B2	30-10-1998
			KR 9209420 B1	16-10-1992
			US 5160701 A	03-11-1992
US 4994238	A	19-02-1991	AT 127228 T	15-09-1995
			AT 148944 T	15-02-1997
			CA 1340389 A1	09-02-1999
			DE 68923996 D1	05-10-1995
			DE 68923996 T2	11-04-1996
			DE 68927777 D1	27-03-1997
			DE 68927777 T2	12-06-1997
			EP 0345781 A2	13-12-1989
			EP 0654659 A1	24-05-1995
			ES 2077571 T3	01-12-1995
			ES 2100091 T3	01-06-1997
			JP 2059648 A	28-02-1990
			JP 2644331 B2	25-08-1997
US 5451350	A	19-09-1995	DE 4217733 A1	02-12-1993
			DE 59307620 D1	11-12-1997
			EP 0571940 A1	01-12-1993
			ES 2109391 T3	16-01-1998
			JP 2604959 B2	30-04-1997
			JP 7092156 A	07-04-1995
EP 0759555	A	26-02-1997	AU 712285 B2	04-11-1999
			AU 6085996 A	06-02-1997
			BR 9603273 A	12-05-1998
			CA 2182545 A1	04-02-1997
			CZ 9602284 A3	12-03-1997
			EP 0759555 A2	26-02-1997
			HU 9602138 A2	28-04-1997
			JP 9163999 A	24-06-1997
			NO 963207 A	04-02-1997
			NZ 299104 A	27-04-1998
			PL 315493 A1	17-02-1997
			RU 2178564 C2	20-01-2002
			SG 47165 A1	20-03-1998
			TR 970201 A1	21-03-1997
			US 5843691 A	01-12-1998
			ZA 9606614 A	02-02-1998
WO 9932883	A	01-07-1999	AU 2005399 A	12-07-1999
			EP 1038176 A2	27-09-2000
			JP 2001527216 T	25-12-2001
			WO 9932883 A2	01-07-1999
			US 6162639 A	19-12-2000
			US 6455324 B1	24-09-2002

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No  
PCT/US 02/29327

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 6162639	A	19-12-2000	US 6455324 B1 24-09-2002
			AU 2005399 A 12-07-1999
			EP 1038176 A2 27-09-2000
			JP 2001527216 T 25-12-2001
			WO 9932883 A2 01-07-1999